

## Industrial Grade Single Parameter Air Quality Monitor



AQBot™ is an industrial air quality monitor with automation capabilities. AQBot™ Series offers a wide range of air quality parameters to choose from. The range of available parameters consists of all the important Gases, Particulates, and Noise related monitoring for Industrial scenarios. AQBot™ product range consists of critical ambient parameters and toxic gases like Total Volatile Organic Compounds (TVOC), Ammonia (NH<sub>3</sub>), Hydrogen sulfide (H<sub>2</sub>S), Methane (CH<sub>4</sub>), Carbon Monoxide (CO), Formaldehyde (CH<sub>2</sub>O), Particulate Matter (PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>10</sub>, PM<sub>100</sub>), Ambient Noise, etc. The AQBot series is designed for easy and inexpensive maintenance.

### Product Features



On Device Display



Ultimate Durability



Weatherproof Enclosure



Compact and Lightweight



Internal Data Storage



SMS and Email Alerts



Real-Time Data



Built-in Relay



Wired Communications



Wireless Communications



Over-The-Air Updates



Data Analytics Software

### Why Monitor Nitric Oxide?

NO (nitric oxide or nitrogen monoxide) is a colorless, non-flammable, oxidizing, poisonous gas with a slightly irritating odour. It consists of one nitrogen atom bonded to one oxygen atom. It is highly reactive due to the presence of one unpaired electron. Thus, this results in rapid oxidation (within a few minutes) to form NO<sub>2</sub>. The main effect of breathing in raised levels of nitrogen dioxide results in an increased likelihood of respiratory problems. Also, NO<sub>2</sub> inflames the lining of the lungs, and it can reduce immunity and cause lung infections. Sources of NO<sub>x</sub> include petrol and metal refining, food processing, and manufacturing industries such as the production of fertilizers. Necessary precautionary measures should be taken by authorities to ensure the health and safety of the workers in the workplace as per HSE guidelines.

### Product Applications



**Textiles Industry**  
Sizing process



**Thermal Power Plants**  
Natural gas/oil/coal based fuel combustion.



**Fisheries Industry**  
From rotting of fish in storage and processing

# AQBot™ NO

## The best in class Nitric Oxide Monitor

AQBot™ consists of the NEMA 4X approved enclosure to last long in a harsh industrial environment. It offers all industry-standard output signals like MODBUS, CANbus, RS-485, RS-232, etc. In addition, the fixed air quality monitor can also offer other communication modes like GSM, GPRS, 3G, WiFi, LoRa, Ethernet, etc. The monitor can easily integrate with existing building monitoring or plant control systems infrastructure. Using such a wide range of communication capabilities, AQBot™ enables the Industrial Internet Of Things (IIoT) which is the backbone of Industrial Revolution 4.0. Using such a wide range of communication capabilities, AQBot™ enables the Industrial Internet Of Things (IIoT) which is the backbone of Industrial Revolution 4.0.

### Key Benefits

- Quick sensing for threshold based alerts
- Highly accurate data to detect low ppb concentrations
- Robust built to sustain harsh industrial conditions
- Easy data integrations to match industry standards
- In-built relay operation for automation
- Data transmissions through multiple channels
- Real time data display for keeping a check
- Siren and strobe for audio and visual alerts
- Effortless installations with versatile mounting arrangement

### AQBot Specifications

ID	PARAMETER	RANGE	RESOLUTION
OZNO_1	Nitric Oxide (NO)	0-20 ppm	0.001 ppm
OZNO_2		0-100 ppm	0.5 ppm



### Electrochemical Sensing

#### TECHNICAL

Processor	Quad-Core ARM Cortex A-72
Memory	2GB RAM, 8GB eMMC ROM
Internal Data Storage	Up to 12 months
Device Interface	On-device software, API, Display
Display Specification	6 digit 7 Segment Display

#### ELECTRICAL

Power Supply	AC: 90VAC- 265VAC 50/60Hz
Power consumption	3.5 W (average)
Wiring connections	Pre-wired supplied with 2m cable

#### GENERAL PERFORMANCE

Operation temperature	-20 to +60°C
Operation humidity	0 - 90%RH, non-condensing
Storage conditions	10 - 40°C
Net Weight	2.8 kg
Dimensions	210mm (W) × 258mm (H) × 105mm (D)
Installation method	Wall mount / Pole mount
Housing	NEMA-4X Fire-retardant FRP enclosure
Weather Protection	Weather Resistant IP66 Enclosure

#### COMMUNICATION

Wireless Communications	Global 2G/3G/4G, LoRa, LTE, NB-IoT, Sigfox, Wifi (Any one)
Wired Communications	Ethernet, MODBUS TCP, MODBUS RTU, RS-485, CANbus (Any one)
Analog Output	1 x 4~20mA Current Loop with 12-bit Resolution
Relay Outputs	2 programmable relays, volt free relay contacts (1NO, 1 NC)
Beacon/sounder	Built-in, RED flashing light with alarm sounder 95db @ 1m

#### SENSING

Gas sample mode	Natural diffusion
Warm up time	1 hour (cold start) for gas monitoring
Response Time (T90)	< 60 Seconds
Signal refresh rate	5 Seconds
Accuracy	<±5%FS (at 20±5°C/ 50±20%RH)
Sensor life	2 years

## Accurate Air Quality Monitoring And Advanced Data Analytics



306, Indraprasth Corporate,  
Prahlanagar, Ahmedabad - India  
✉ [contact@oizom.com](mailto:contact@oizom.com) / [connect@oizom.com](mailto:connect@oizom.com)  
☎ +91-8866660025 /39